List Prices for pHionics STs Series™

All instruments come standard with a secondary 0-50°C temperature sensor and a 25 ft. (7.62 m) cable.

Model #	Parameter	Range	Price (USD)
1014	**pH**	0-14 pH*	930
1611		6-11 pH	1030
2001	**ORP (redox)**	-1000 to +0 mV	980
2100		+0 to +1000 mV*	980
2101		-1000 to +1000 mV*	980
2505		-500 to +500 mV	980
3020	**Dissolved Oxygen**	0-20 mg/L*	1280
4102	**Conductivity**	0-100 µS/cm	1150
4202		0-200 µS/cm	1150
4502		0-500 µS/cm	1150
4103		0-1000 µS/cm*	1150
4203		0-2000 µS/cm	1150
4503		0-5000 µS/cm*	1150
4104		0-10,000 µS/cm*	1150
4204		0-20,000 µS/cm	1150
4504		0-50,000 µS/cm	1150
4105		0-100,000 µS/cm*	1150

* indicates the ranges normally stocked

Housing Material

s	316 Stainless Steel	N/C
t	Titanium	Add 200

Connection

025	25 ft. (7.62 m) Cable	N/C
nnn	nnn ft. Custom Length Cable	Add 50+3 per foot

Cables are polyurethane-coated, shielded, Kevlar-reinforced, and water-blocked.

STs_____-_____

Example: STs1014s-025 for a 0-14 pH sensor with 316 Stainless Steel housing and standard cable.

Contact us:

sales@phionics.com or 1 (775) 339-0565

Use the generated product number to clearly indicate which product options you are interested in.

Payment methods accepted include U.S. credit cards and wire transfers. Orders are shipped 3-5 business days after payment is received unless otherwise noted.

Copyright © 2021 pHionics Inc. All rights reserved. Prices subject to change.