

## List Prices for phionics STs Series™ 4-20 ma 2-Channel Transmitters

All transmitters come standard with a 0 to 50 °C temperature output on Channel 2  
and the choice of a DIN connector or 25 foot(7.6 meters)cable

STs 1014s - 025

Model	Parameter	Range	Price (USD)
<b>1014</b>	pH	0 to 14 pH	Stocked* <b>930</b>
<b>1611</b>		6 to 11 pH	<b>1030</b>
<b>2100</b>	ORP (redox)	0 to +1000 mv	Stocked <b>980</b>
<b>2505</b>		-500 to +500 mv	<b>980</b>
<b>2101</b>		-1000 to +1000 mv	Stocked <b>980</b>
<b>2001</b>		0 to -1000 mv	<b>980</b>
<b>3020</b>	Dissolved Oxygen	0 to 20 mg/l	Stocked <b>1090</b>
<b>4102</b>	Conductivity	0 to 100 uS	<b>1150</b>
<b>4202</b>		0 to 200 uS	<b>1150</b>
<b>4502</b>		0 to 500 uS	<b>1150</b>
<b>4103</b>		0 to 1000 uS	Stocked <b>1150</b>
<b>4203</b>		0 to 2000 uS	<b>1150</b>
<b>4503</b>		0 to 5000 uS	Stocked <b>1150</b>
<b>4104</b>		0 to 10,000 uS	Stocked <b>1150</b>
<b>4204</b>		0 to 20,000 uS	<b>1150</b>
<b>4504</b>		0 to 50,000 uS	<b>1150</b>
<b>4105</b>		0 to 100,000 uS	Stocked <b>1150</b>

### Housing Material

<b>s</b>	316 SS	n/c
<b>t</b>	Titanium	<b>Add 200</b>

### Cable or DIN Connector

<b>DIN</b>	1.0 inch NPT PVDF Fitting with DIN connector (Replaces Cable)	n/c
<b>025</b>	25 feet (7.6 meters) standard polyurethane cable	n/c
<b>nnn</b>	Replace 'nnn' with feet of poly cable	

**Add \$50 plus \$3.00/ft**

\* Ranges typically stocked. There may be shortages due to demand.  
Returned sales may be subject to a 20% of list price restocking fee  
due to testing required to confirm proper operation.

All prices in U.S. Dollars.



1.775.339.0565 e-mail: sales@phionics.com